



ACCULASE-GPA

Tunable Diode Laser

PROTECH903

Tape

BRIMSTONE

Spectrophotometer

ACCUCHROME GC

TCD

GASMICRO

EVC- EPR

GASMICRO NG

Next Gen EVC-EPR

FEATURES

- 0.15 ppm Sensitivity
- No Scrubber
- Up to 4 Streams
- No Consumables
- Low Maintenance

- ± 5 ppb Sensitivity
- Predictive Alarm
- Extended-Life Tape
- Combined H₂S / TS
- No Interferences

- < 10 Sec. Response
- No Interferences
- Anti-Clogging Probe
- No Calibration Gas
- Double Air Demand

- ±0.25 Btu Accuracy
- 4 Minutes Analysis
- Up to 8 Streams
- CSA Class 1 Div. 1
- Optional C9+ Analysis

- ± 0.05% Accuracy
- CSA-400 to +650C
- 12 Year Calibration
- 8 Year Data Back-Up
- 1 Wide-Range Sensor

- 40C to 70C Operation
- Smart Plug and Play Pressure Transducers
- Advanced Reverse Flow and Rocking Detecting Algorithms

APPLICATIONS

- Custody Transfer
- Pipeline / Processing
- Measures H₂S, CO₂, H₂O in a single gas cell

- Catalyst Protection
- Refinery Flare
- Natural Gas Processing
- Petrochemical Feedstocks

- Tail Gas Air Demand
- SRU Sulfur Pit
- SRU Acid Gas Feed

- Refinery Flare
- N.G. Pipeline
- Custody Transfer

- N.G. Distribution
- Custody Transfer
- Energy Management

- Meter Correction for Natural Gas Distribution

PARAMETERS

- H₂S
- H₂O
- CO₂

- Hydrogen Sulfide
- Total Sulfur
- Arsine
- Phosphine
- Phosgene
- Chlorine

- Hydrogen Sulfide
- Sulfur Dioxide
- Carbonyl Sulfide
- Carbon Disulfide

- C6+ or C9+ Analysis
- H₂ and O₂ Optional
- Heating Value
- Specific Gravity
- Wobbe Index

- Volume
- Pressure
- Temperature

- Pressure
- Temperature
- Corrected Volume





ACCUSERIES-LPA

Titration, ISE, Colorimeter



FPA 4100

UV- VIS Photometer



MONITEK

Turbidity- TSS- Color



**MONITEK
ULTRASONIC**

Acoustic Oil in Water
/ TSS



VISCOSITE

Torsional Oscillation
Viscosity

FEATURES

- ± 2 ppb Sensitivity
- Div. 2 / Zone 2 (No Purge)
- Multi-Parameter / Stream
- Custom Wetted Parts
- Handles 700C Sample

- Multi-Stream Up to 8
- IECEx Zone 1 (No Purge)
- Accessible External Cell
- Auto Zero / Calibration

- Powerful Cleaning Jets
- Div. 1 / Zone 1 Sensors
- 1,400 psi / ≤ 100 m Cable
- Custom Connections / Units
- Submersible or Flanged

- Handles Coatings on Sensor
- 0 Downtime Sensor Removal
- Div.1/Zone 1/CRN Sensors
- 1500C / 260 psi Samples

- No Moving Parts
- Div. 1 / Zone 1 Sensor
- 4000C / 2,500 psi
- Anti-Stick Teflon Coating
- Sensor Shield Protection

APPLICATIONS

- Amine Sweetening
- Sour Water Stripper
- Hardness in Brine

- H₂S / SO₂ in Gas
- Waste Water Deodorizing
- Oil in Water

- NGL Saybolt Color
- Polymer Dosing Control
- Chor-Alkali Brine Clarity

- Filter Break-Through
- Oil in Water
- TSS in Edible Oil Processing

- Roofing Asphalt
- Ceramic Cement
- Refinery Vis-Breaking

PARAMETERS

- Acid # / Base #
- Alkalinity
- Ammonia / Ammonium
- Chloride
- Hardness
- Hypochlorite
- H₂S
- ... And more

- Oil in Water
- H₂S
- SO₂
- Nitrate
- Chlorine
- ... And more

- Suspended Solids
- Turbidity
- Color

- Suspended Solids
- Oil in Water

- Viscosity

